

# SVAN 955

## Sound Level Meter

*The SVAN 955 is all digital, Type 1 sound level meter. Instrument is intended to general acoustic measurements, environmental noise monitoring, occupational health and safety monitoring.*

*Three acoustic profiles allow parallel measurements with independently defined filters and RMS detector time constants. Each profile provides significant number of results (like  $L_{eq}$ ,  $L_{Max}$ ,  $L_{Min}$ ,  $L_{Peak}$ ,  $Spl$ ,  $SEL$  etc.). Advanced time history logging for each profile provides complete information about measured signal in non-volatile 16 MB internal memory or external USB Memory Stick and can be easily downloaded to any PC using USB interface and SvanPC+ software.*

*Acoustic dosimeter function is available with the SV 25 dedicated microphone. Fast USB 1.1 interface (12 MHz) creates real time link for the PC "front-end" application of the SVAN 955 instrument. It can be controlled and the measurement results can be also downloaded to any PC using the RS 232 or IrDA interfaces. Instrument is powered from four AA standard or rechargeable batteries (separate charger is required). The powering of the instrument from the External DC power source or USB interface is also provided.*

*Robust case and light weight design accomplish the exceptional features of this new generation instrument.*

## FEATURES

- Type 1 sound level measurements meeting IEC 61672:2002
- Single measurement range
- Three parallel independent profiles
- Advanced Data Logger, up to 12 results logged simultaneously
- Time History recording on USB Memory Stick providing almost unlimited logging capacity
- Acoustic dose meter
- Advanced trigger and alarm functions
- USB 1.1 interface  
(real time PC "front end" application)
- USB 1.1 Host interface
- RS 232 and IrDA interfaces
- Integration time programmable up to 24 h
- Power supply by four AA rechargeable or standard batteries
- Hand held, light weight and robust case
- Easy in use



# TECHNICAL SPECIFICATIONS

## SOUND LEVEL METER

Standards	Type 1: IEC 61672-1:2002
Meter mode	$L_{eq}$ , $Spl$ , $SEL$ , $L_{EP,d}$ , $L_{den}$ , $L_{tm3}$ , $L_{tm5}$ , Statistics - $L_n$ ( $L_1$ - $L_{99}$ ), $L_{Max}$ , $L_{Min}$ , $L_{Peak}$ Simultaneous measurement in three profiles with independent set of filters and detector time constants
Weighting Filters	A, C and Z
RMS Detector	Digital True RMS detector with Peak detection, resolution 0.1 dB Time Constants: Slow, Fast, Impulse
Microphone	7052, nominal sensitivity 22 mV/Pa, prepolarised 1/2" condenser microphone
Measurement Range	Total Dynamic Range: 18 dBA RMS ÷ 141 dBA Peak Linearity Range: 25 dBA RMS ÷ 141 dBA Peak
Dynamic Range	120 dB
Internal Noise Level	less than 18 dBA RMS
Data Logger*	Time History logging of RMS / Max / Min / Peak results to internal memory or USB Memory Stick (USB Host option) with logging step down to 2 ms. Up to 12 measurement results logged simultaneously (option)
Acoustic dose meter*	Acoustic dose meter meeting IEC 61252 with SV 25 microphone (option)


## BASIC DATA

Input	IEPE with TNC connector (SV 12L IEPE preamplifier)	
Display	LCD 128 x 64 pixels plus icons with backlighting	
Memory	16 MB non-volatile flash type, USB Memory Stick (option)	
Interfaces	USB 1.1 Client, USB 1.1 Host (option), RS 232 (with SV 55 option), IrDA (with USB Host option) External I/O - AC output (1 V Peak) or Digital Input/Output (Trigger - Pulse)	
Power Supply	Four AA batteries (alkaline)	operation time > 12 h (6.0 V / 1.6 Ah)**
	Four AA rechargeable batteries	operation time > 16 h (4.8 V / 2.6 Ah)**
	SA 17A external battery pack (option)	operation time > 24 h**
	External power supply	6 V DC ÷ 15 V DC (1.5 W)
	USB interface	500 mA HUB
Environmental Conditions	Temperature	from -10 °C to 50 °C
	Humidity	up to 90 % RH, non-condensed
Dimensions	335 x 82 x 42 mm (with microphone and preamplifier)	
Weight	610 grams with batteries, microphone and preamplifier	


\*each function parallel to the meter mode \*\*with USB 1.1 Host function not active and backlight off



Main result in one profile view



Main results in 3 profiles view



Time history plot

Continuous product development and innovation are the policy of our company. Therefore, we reserve the right to change the specifications without prior notice.

DISTRIBUTOR:



SVANTEK Sp. z o. o.  
Pl. Inwalidów 3/62  
PL 01-514 WARSAW, POLAND  
phone/fax (+48) 22 839 00 31, (+48) 22 839 64 26  
<http://www.svantek.com> e-mail: [office@svantek.com.pl](mailto:office@svantek.com.pl)

ISO 9001  
CERTIFIED

苏州声和振动科技有限公司 (SuZhou SV Technology CO., LTD)

地址: 江苏苏州东吴北路 31 号

电话: 0512-67071025/67071026 传真: 0512-66351026

网址: <http://www.sv-china.com> 邮编: 215128